Module 8.5: Dataset augmentation

Different forms of regularization

- l_2 regularization
- Dataset augmentation
- Parameter Sharing and tying
- Adding Noise to the inputs
- Adding Noise to the outputs
- Early stopping
- Ensemble methods
- Dropout

Different forms of regularization

- l_2 regularization
- Dataset augmentation
- Parameter Sharing and tying
- Adding Noise to the inputs
- Adding Noise to the outputs
- Early stopping
- Ensemble methods
- Dropout






label = 2




label = 2







label = 2









rotated by 65°




label = 2













label = 2







rotated by 65°



shifted vertically




label = 2

 $[{\rm given}\ {\rm training}\ {\rm data}]$




shifted horizontally






label = 2

 $[{\rm given}\ {\rm training}\ {\rm data}]$






label = 2




label = 2

label = 2



label = 2

[augmented data = created using some knowledge of the task




label = 2



label = 2

[given training data] We exploit the fact that certain transformations to the image do not change the label of the image.



label = 2

[augmented data = created using some knowledge of the task]

• Typically, More data = better learning

- Typically, More data = better learning
- Works well for image classification / object recognition tasks

- Typically, More data = better learning
- Works well for image classification / object recognition tasks
- Also shown to work well for speech

- Typically, More data = better learning
- Works well for image classification / object recognition tasks
- Also shown to work well for speech
- For some tasks it may not be clear how to generate such data